Web Images Videos Maps News Shopping Gmail more ▼ Sign in Advanced Scholar Search Scholar Preferences GOOXIC SCHOlar | combining cad models +errors Search Scholar Articles and patents Results 1 - 10 of about 35,600. (0.19 sec) anytime include citations repri Modeling, combining, and rendering dynamic real-world events from image ... psu.edu [PDF] S Vedula, P Rander, H Saito, T Kanade - Proc. 4th Conference on Virtual ..., 1998 - Citeseer ... 4.2 Combining a Virtualized Reality Representation with a Virtual Model ... The Virtualized Reality models combined in Section 4.1 into a sequence of polygonal meshes are textured and introduced into a CAD model of a virtual basketball court, to generate a unified geometry ... Cited by 58 - Related articles - View as HTML - All 12 versions Bayesian analysis of stochastic volatility models with fat-tails and correlated errors harrisd.net (Pt E Jacquier, NG Polson, PE Rossi - Journal of Econometrics, 2004 - Elsevier ... one of the financial series show strong evidence of fat-tailed conditional mean errors, albeit weaker ... the fat-tail and correlation extensions separately and then observe that they are easy to combine. ... In the context of stochastic volatility models, Geweke (1994c) and Gallant et al. ... Cited by 159 - Related articles - All 17 versions [PDF] From engineering drawings to 3 D CAD models: are we ready now? technion.ac.il D Dori, K Tombre - Computer Alded Design, 1995 - dori2.technion.ac.il ... cad, paper and raster drawings are thus three versions of an engineering drawing model, which may also be classified as ... Human performance and 3D cad conversion A trained human expert reconstructs the 3D geometry of the object (part or assembly) by combining in his ... Cited by 74 - Related articles - BL Direct - All 5 versions MMR: An interactive massive **model** rendering system using geometric and image- ... psu.edu (PDF) DiAliaga, Ji Cohen, A Wilson, E Baker, H... - Proceedings of the ..., 1999 - portal.acm.org ... Our system automatically balances the screen-space errors resulting from geometric simplification with those ... Any general system for interactive walkthroughs should **combine** such techniques. ... another system, for visualizing power generation engines and aircraft CAD models. ... Cited by 150 - Related articles - All 15 versions рен Methods and algorithms of automated CAD repair for incremental surface ... psu.edu [PDF] AA Mezentsev, T Woehler - Proceedings 8th International Meshing ..., 1999 - Citeseer ... The general tendency is that technical systems are becoming more interdisciplinary, combining subsystems of differing physical nature. ... However, the BREP CAD models can contain errors, such as gaps, incorrect topology of trimming curves[5]; these errors are caused by ... Cited by 34 - Related articles - View as HTML - All 6 versions Going out: Robust model-based tracking for outdoor augmented reality psu.edu [PDF] G Reitmayr, T Drummond - Proceedings of the 2006 Fifth IEEE and ..., 2006 - portal.acm.org ... [33] describe a hybrid tracking system for outdoor AR combining optical tracking and inertial sensors. ...  $C = (J T \text{ diag}(\sigma) - 1 J) - 1 . (8) 3.2 \text{ Samples from a textured 3D model}$  The original version of the edge-based tracking system used a CAD model of salient edges of the scene ... Cited by 99 - Related articles - All 9 versions of soft tissue artefact in motion analysis by **combining** 3D fluoroscopy and ... R Stagni, S Fantozzi, A Cappello, A Leardini - Clinical Biomechanics, 2005 - Elsevier ... Quantification of soft tissue artefact in motion analysis by combining 3D fluoroscopy and stereophotogrammetry ... These large errors can nullify the usefulness of these variables in the clinical ... was reconstructed by means of the 2D fluoroscopic projections and CAD models of the ... Cited by 41 - Related articles - All 10 versions The pre-processing of data points for curve fitting in reverse engineering MC Huang, CC Tai - The International Journal of Advanced ..., 2000 - Springer ... By combining individual curves to construct all of the surfaces, designers may effortlessly achieve a complete CAD model conforming to the design intent. Additionally, some regression errors are introduced by the regression operation between the measured points and the ... Cited by 54 - Related articles - BL Direct - All 3 versions Combining 2D and 3D views for orientation and relative position tasks psu.edu [PDF]

1 of 2 3/9/10 11:24 AM

M Tory, T Moller, MS Atkins, AE ... - Proceedings of the ..., 2004 - portal acm.org

usc.edu [PDF]

... For this reason, **CAD models** are usually displayed from several viewpoints at once, often from three ... icon displays and therefore did not consider the question of how to best **combine** 2D and ... would be fastest, but estimating height would be difficult so there would be many **errors**. ... Cited by 22 - Related articles - All 13 versions

## [PDF] Approaches to large-scale urban modeling

J Hu, S You, U Neumann - IEEE Computer Graphics and ..., 2003 - graphics.usc.edu

... Combining the two systems increased the accuracy and lowered the cost of obtaining aerial Lidar data. ... image sensors, aeri- al active sensors, and 2D footprint data from GIS or CAD data. ... Users can find errors by projecting models onto images or images as textures onto models ... Cited by 73 - Related articles - View as HTML - BL Direct - All 7 versions

combining cad models +errors

Go to Google Home - About Google - About Google Scholar

Search

©2010 Google

2 of 2 3/9/10 11:24 AM